DATA SHEET

soniflex.

soni VLD felt tapes

Our **soni VLD felt tapes** are ideal for neatly masking edges or taping over joints of our range of colored acoustic products.

The adhesive tapes are available in the same colors as our sound absorbers soni COLOR, soni COLOR RD, soni ELEMENT, soni DESK PARTITION, soni ROOM DIVIDER OR SONI PORTA.

Our **soni VLD felt tapes** score with a high adhesive strength and excellent durability. The inserted scrim reinforcement prevents stretching.

► Basis of adhesive: acrylate



soni VLD felt tapes

TECHNICAL DATA				
FLAMMABILITY	► Fulfills the strict fire safety standard for the automotive industry (FMVSS 302, DIN 75 200) ► ISO 3795, burning rate < 100 mm/min			
TEMPERATURE RESISTANCE	▶-30°C to +80°C			
COLOR FASTNESS TEST OF FELT COVER	▶ DIN EN ISO 105-B02: 6-7			
ABRASION RESISTANCE OF FELT COVER	▶ISO 12947-2: > 50.000 rubs			
ADHESIVE STRENGTH / CPA-4.01	► Self-adhesive layer on steel plate: at least 35 N / 5 cm			

DIMENSIONS					
	PRODUCT	THICKNESS / TOLERANCE [mm]	width [mm]	RUNNING LENGTH	
	VLD felt tapes	0.3 ± 0.1	40 and 60	10 m/reel	

BENEFITS

- ► High flexibility for effortless application around edges
- ► High durability
- ► Excellent adhesion
- ► Attractive color selection the perfect match for our colored acoustic products.





















PLEASE SEE OUR PROCESSING AND STORAGE INSTRUCTIONS

Details and values given in this leaflet are average values and have been compiled with care. They are not binding, however, and Cellofoam International GmbH & Co. KG disclaims any liability for any damages and detriments, also in connection with any third party's rights. The information given does not release the buyers from making the necessary experiments and tests themselves. Subject to technical changes. For updates please go to our website.

Cellofoam International GmbH & Co. KG Business unit soniflex P: +49 7351 340 28 61 sales@soniflex.de / www.soniflex.de

VERSION 07/21